



PALLET BOARD STACKER WITH CROSSCUT SAW PBS M4 + DS-1.0

QUALITIES

- 3 side pneumatic layer alignment
- Stacking options: Straight, straight offset, diagonal offset (optional)
- Complete package setting: the lift is full or by entering the required number of rows

PBS M4 PROVIDES

- The effective unscrambler allows to integrate pallet board stacker straight into board production line; – 7 sec to elevate to the working height.

QUALITIES

- Easily integrated directly into the board stacker line, operates at the stacker speed
- Intended for board length cutting and end trimming
- Compact and practical design for easy maintenance
- Quick blade lifting if any of the saws is not in use
- Synchronized blade and chain module repositioning according to the position indicator
- Chip and offcut conveyor

TECHNICAL DETAILS

Power	8,6 kW
Pneumatic pressure	4-6 bar
Dimensions	8 m x 3,2m x 3m

TECHNICAL DETAILS

Sawblade diameter(mm)	350
Power per sawblade(kW)	3
Feed speed(m/min)	50
Total power(kW)	7,1
Chip suction pipe diameter(mm)	80 x 2gb

WORK MATERIAL

Max length	800-1800 mm
Min width	60-160 mm
Max. material thickness	50 mm
Min. material thickness	13 mm

